



短节距精密滚子链链轮

Short pitch precision roller chain wheels


| 1"1/2X1" 24A-1-2-3 GB1244-1997 DIN8187 ISO/R606 | | 链轮齿部参数MM | | |
|---|----|----------|-----|-------|
| | | 节距 | P | 38.1 |
| | | 滚子直径 | d-φ | 22.23 |
| | | 元弧半径 | r3 | 40.5 |
| | | 倒角宽度 | C | 4.8 |
| | | 齿宽 | B1 | 23.5 |
| | | 齿宽 | b1 | 22.9 |
| 齿宽 | B2 | 68.89 | | |
| 齿宽 | B3 | 114.33 | | |



A型单排平片链轮
A type simplex plate wheels



A型双排平片链轮
A type duplex plate wheels



A型叁排平片链轮
A type triplex plate wheels

| 齿数 Z | 外径 de | 节径 dp | 单排链轮 | | | 双排链轮 | | | 叁排链轮 | | |
|---------|----------|----------|---------|----|----|--------|----|-----|---------|----|---|
| | | | Simplex | | | Duplex | | | Triplex | | |
| | | | dm | D1 | A | dm | D2 | A | dm | D3 | A |
| 8 | 115 | 99.55 | 58 | 20 | 45 | | | | | | |
| 9 | 126.4 | 111.4 | 70 | 20 | 45 | | | | | | |
| 10 | 138 | 123.29 | 80 | 20 | 45 | 80 | 25 | 95 | | | |
| 11 | 150 | 135.21 | 90 | 25 | 50 | | | | | | |
| 12 | 162 | 147.22 | 102 | 25 | 50 | 102 | 25 | 100 | | | |
| 13 | 174.2 | 159.18 | 114 | 25 | 50 | | | | | | |
| 14 | 186.2 | 171.22 | 128 | 25 | 50 | 128 | 25 | 100 | | | |
| 15 | 198.2 | 183.26 | 132 | 25 | 50 | 132 | 25 | 100 | | | |
| 16 | 210.3 | 195.3 | 136 | 25 | 55 | 136 | 30 | 100 | | | |
| 17 | 222.3 | 207.34 | 140 | 25 | 55 | 136 | 30 | 100 | | | |
| 18 | 234.3 | 219.42 | 140 | 25 | 55 | 160 | 30 | 100 | | | |
| 19 | 246.5 | 231.49 | 140 | 25 | 55 | | | | | | |
| 20 | 258.6 | 243.57 | 140 | 25 | 55 | | | | | | |
| 21 | 270.6 | 255.65 | 150 | 30 | 60 | | | | | | |
| 22 | 282.7 | 267.73 | 150 | 30 | 60 | | | | | | |
| 23 | 294.8 | 279.8 | 150 | 30 | 60 | 160 | 30 | 100 | | | |
| 24 | 306.8 | 291.88 | 150 | 30 | 60 | | | | | | |
| 25 | 319 | 304 | 150 | 30 | 60 | | | | | | |
| 26 | 331 | 316.08 | 150 | 30 | 60 | | | | | | |
| 27 | 343.2 | 328.19 | 150 | 30 | 60 | | | | | | |
| 28 | 355.2 | 340.27 | 150 | 30 | 60 | | | | | | |
| 29 | 367.3 | 352.38 | 150 | 30 | 60 | | | | | | |
| 30 | 379.5 | 364.5 | 150 | 30 | 60 | 160 | 30 | 100 | | | |
| 31 | 391.6 | 376.62 | 150 | 30 | 60 | | | | | | |
| 32 | 403.7 | 388.69 | 150 | 30 | 60 | | | | | | |
| 33 | 415.8 | 400.81 | 150 | 30 | 60 | | | | | | |
| 34 | 427.8 | 412.93 | 150 | 30 | 60 | | | | | | |
| 35 | 440 | 425.04 | 150 | 30 | 60 | | | | | | |
| 36 | 452 | 437.16 | 150 | 30 | 60 | | | | | | |
| 37 | 464.2 | 449.27 | 150 | 30 | 60 | | | | | | |
| 38 | 476.2 | 461.39 | 150 | 30 | 60 | | | | | | |
| 39 | 488.5 | 473.5 | 150 | 30 | 60 | | | | | | |
| 40 | 500.6 | 485.62 | 150 | 30 | 60 | | | | | | |

